




Glass & Optical Lens Cleaning Solution Safety Data Sheet






Safety Data Sheet

Part No: US-SO-OPT Solution

Revision Number: 8 2019

Glass & Optical Lens Cleaning Solution

A specialist formulation for adding to Ultrasonic baths for cleaning glass and optical lenses. It safely removes contaminants including general soiling, waxes, buffing compounds, fingerprints and grease etc. and will not damage the glass or any metal parts. Use to restore clarity or as a preparation of surface before applying special coatings.



- Deep cleans removing dirt and grease.
- Excellent stain remover.
- Economical to use.
- For professional and amateur use.



Directions

Concentrate is added to water at a rate of 1 part concentrate to 10 parts of water. Operating temperature of bath should be set between 60 and 80 degrees centigrade.

Solutions should be used with deionised, demineralised or distilled water as Calcium carbonate and other impurities in tap water can effect/reduce the cleaning properties of the solutions and produce undesirable side effects such as deposits

Always test before use on new applications.

After cleaning rinse all surfaces thoroughly with clean water. The bath should be changed regularly when the solution becomes dirty.

Other Ultrasonic Solutions Available

There are a variety of ultrasonic solutions available, formulated for specific applications. Correct selection is vital to give optimal performance and prevent an adverse reaction.

Solutions include;

- Jewellery.
- •Glass and optical lens.
- General Purpose Degrease.
- Oxidation Remover.
- Sensitive Metals.
- Carburettor and engine parts.







Section 1: Identification of the substance/mixture and company/undertaking

I.I. Product identifier

Product name: ULTRASONIC CLEANER FOR CARBURETTORS AND MACHINE PARTS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC35: Washing and cleaning products (including solvent based products).

1.3. Details of the supplier of the safety data sheet

Allendale Ultrasonics Company name:

> Pindar Road Hoddesdon Herts ENII 0BZ United Kingdom

Tel: +44 (0) 1992 455925

Fax: +44 (0) 1992 450781

Email: technical@allendale-ultrasonics.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 448 706 266 NHS DIRECT - 0845 4647 OR 111

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe skin burns and eye damage.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

Hazard pictograms: GHS05: Corrosion

Signal words: Danger









Precautionary statements:

P260: Do not breathe fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

2-BUTOXYETHANOL

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|----------|-----------|---|---------|
| 203-905-0 | 111-76-2 | | Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315 | 1-10% |

ALCOHOLS, C12-13- BRANCHED AND LINEAR, ETHOXYLATED (>5 - <15 EO)

| 931-954-4 | 160901-19-9 | - | Acute Tox. 4: H302; Eye Dam. 1: H318; | 1-10% |
|-----------|-------------|---|---------------------------------------|-------|
| | | | Aquatic Chronic 3: H412 | |
| | | | | |

PROPAN-2-OL

| 200-661-7 | 67-63-0 | Flam. Liq. 2: H225; Eye Irrit. 2: H319; | 1-10% |
|-----------|---------|---|-------|
| | | STOT SE 3: H336 | |
| | | | |

DISODIUM METASILICATE

| 229-912-9 | 6834-92-0 | - | Skin Corr. 1B: H314; STOT SE 3: H335 | 1-10% |
|-----------|-----------|---|--------------------------------------|-------|
| | | | | |

2-AMINOETHANOL

| 205-483-3 | 141-43-5 | Acute Tox. 4: H332; Acute | Tox. 4: H312; <1% |
|-----------|----------|-----------------------------|-------------------|
| | | Acute Tox. 4: H302; Skin Co | orr. 1B: |
| | | H314 | |
| | | | |



Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. Give I cup of water to drink Blistering may occur. Progressive ulceration will occur if treatment is not immediate. every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact:

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire fighters

Advice for fire fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.





Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.#

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well-ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.







Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2-BUTOXYETHANOL

Workplace exposure limits: Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------|--------------|------------|--------------|
| UK | 25 ppm | 50 ppm | - | - |

PROPAN-2-OL

| UK | 999 mg/m3 | 1250 mg/m3 - | - |
|----|-----------|--------------|---|
| | | | |

2-AMINOETHANOL

| UK | 2.5 mg/m3 | 7.6 mg/m3 | - | - |
|----|-----------|-----------|---|---|
| | | | | |

DNEL/PNEC Values DNEL / PNEC No data available.







8.2. Exposure controls

General protective and hygienic

measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases/ fumes / aerosols. Avoid contact with

the eyes and skin. *

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of

emergency. Must comply to EN137*

Hand protection: Protective gloves – Rubber Gloves (EN 374-2) * The selection of the

suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. The determined penetration times according to EN 374 – part III are not performed under practical conditions. Therefore a maximum wearing

time, which corresponds to 50% of the penetration time, is

recommended. *

Eye protection: Tightly fitting safety goggles. Ensure the goggles have the relevant

markings on them showing which aspect of EN166 they conform to.

Ensure eye bath is to hand. *

Skin protection: Protective clothing - ensure they are suitable for working with liquid

chemicals. *

PERSONAL PROTECTIVE EQUIPMENT SYMBOL(S) *









Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid
Colour: Colourless

Odour: Characteristic odour

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Miscible in all proportions

Viscosity: Non-viscous

Boiling point/range °C: >35* Melting point/range °C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point °C: >60* Part.coeff. n-octanol/water: No data available.

Autoflammability °C: No data available. Vapour pressure: No data available.

Relative density: No data available. pH: >11.5

VOC g/I: No data available.







9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.







Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2-BUTOXYETHANOL

| IVN | RAT | LD50 | 307 | mg/kg |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 1230 | mg/kg |
| ORL | RAT | LD50 | 470 | mg/kg |

PROPAN-2-OL

| IVN | RAT | LD50 | 1088 | mg/kg |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 3600 | mg/kg |
| ORL | RAT | LD50 | 5045 | mg/kg |
| scu | MUS | LDLO | 6 | gm/kg |

DISODIUM METASILICATE

| ORL | MUS | LD50 | 770 | mg/kg |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 1153 | mg/kg |

2-AMINOETHANOL

| IVN | RAT | LD50 | 225 | mg/kg |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 700 | mg/kg |
| ORL | RAT | LD50 | 1720 | mg/kg |
| SCU | RAT | LD50 | 1500 | mg/kg |







Relevant hazards for product:

| Hazard | Route | Basis |
|-------------------------------|-------|-----------------------|
| Skin corrosion/irritation | DRM | Hazardous: calculated |
| Serious eye damage/irritation | OPT | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth

or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or

wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.



Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number (ADR/RID): 1760*

UN number (IMDG): 1760*

UN number (ICAO): 1760*

1760* **UN** number (ADN):

14.2. UN proper shipping name

Proper Shipping name (ADR/RID): CORROSIVE LIQUID, N.O.S. (CONTAINS Alcohols, C12 -13 -branched and linear, ethoxyalted (>5 - <15 EO)) *

CORROSIVE LIQUID, N.O.S. (CONTAINS Alcohols, C12 -13 - branched and linear, Proper Shipping name (IMDG):

ethoxyalted (>5 - <15 EO)) *

Proper Shipping name (ICAO): CORROSIVE LIQUID, N.O.S. (CONTAINS Alcohols, C12 -13 - branched and linear,

ethoxyalted (>5 - <15 EO)) *

Proper Shipping name (ADN): CORROSIVE LIQUID, N.O.S. (CONTAINS Alcohols, C12 -13 - branched and linear,

ethoxyalted (>5 - <15 EO)) *

14.3. Transport hazard class(es)

ADR/RID class:

ADR/RID classification code: C9*

8* ADR/RID label:

8* **IMDG** class:

ICAO class/division:

ADN class: 8*





14.4. Packing group

||* ADR/RID group:

IMDG group: ||*

ICAO group:

ADN group:

14.5. Environmental hazards

Environmentally hazardous: NoMarine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code:

Transport category:

Overland Transport: Category 2*

Transport by Sea: Category 2*

Air Transport: Category 2*

Inland Waterway Transport: Category 2*

Rail Transport: Category 2*

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.









Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 * indicates text in the SDS, which has changed since the last revision.

Phrases used in s.2 and s.3:

H225: Highly flammable liquid and vapour.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product



Contact Details

The Allendale Group Ltd
Allendale-Ultrasonics Dept.
Pindar Road
Hoddesdon
Hertfordshire
ENII 0BZ

+44 (0)1992 455925 sales@allendale-ultrasonics.co.uk www.allendale-ultrasonics.co.uk